

Thank You . . .


for selecting this product for your personal use. NOW, please follow the important instructions and information as illustrated and described

INSTALLATION OF YOUR BROWN BAG SLING

The **Double Helic Barrel Loop** must be installed first on the firearm.

Carefully study the adjoining photograph. Notice how the webbing is coiled around the gun barrel two times. The sling has been sewn together in a manner as to easily achieve this process.

The extended portion (strap) of the sling should be pulled firmly, working to remove all of the slack from the barrel loop. The **Double Helic Barrel Loop** should fit snugly around the firearm barrel without any looseness to acquire a firm grasp around the barrel to prevent slipping. The barrel loops should be positioned on the firearm barrel immediately in front of the fore-end of the firearm.



WARNING

DO NOT attempt to attach your **Brown Bag Sling** onto a loaded firearm--cartridge in chamber. Firearm safety is your responsibility. Check, visually inspect, make sure your firearm is unloaded--chamber empty, magazine empty before attaching **The Brown Bag Sling**.

*Share the pleasure
of your shooting/hunting
activities with someone . . .
they will learn to appreciate
them as you do.*

To obtain a brochure of our other products, please contact us in the method most convenient to you.



201 COTTON DR. • P.O. BOX 7751 • WACO, TX 76714-7751 • USA
254-772-5575 • FAX 254-776-3553 • 1-800-533-6076
WEB SITE: www.OutdoorConnection.com

BUTT STOCK BINDING

Open the butt stock part of **The Brown Bag Sling** to accept the butt of the firearm as shown in the adjoining photograph. Notice one side of the stirrup (strap across the butt plate or pad) will slide along the portion of the webbing that encircles the stock. This is to allow nominal adjustment to center the stirrup in the middle of the butt plate/pad, as pictured.



The extended portion (strap) of **The Brown Bag Sling** should be pulled firmly, working to remove all of the slack from the butt stock binding. The butt stock binding should fit snugly around the stock of the firearm without any looseness to acquire a firm grasp of the stock and to prevent slipping, as pictured.

